

## CANFORD SDV-LFH - HDTV DIGITAL VIDEO CABLE (0.6/2.8) Low fire hazard



36-515 CANFORD SDV-LFH CABLE Green  
36-516 CANFORD SDV-LFH CABLE Turquoise  
36-517 CANFORD SDV-LFH CABLE Violet  
36-519 CANFORD SDV-LFH CABLE Cream

Coaxial 75 ohm cable specifically for serial digital video signals, with compact size and low smoke-zero halogen material outer jacket.

### Technical Specification:

Cable size group:	X
Inner conductor:	0.6mm plain copper
Dielectric:	Foam polyolefin, 2.80mm O.D.
Screen 1:	Aluminium/polyester/aluminium tape longitudinally applied
Screen 2:	0.122mm tinned copper braid, optical coverage 95%
Construction:	Coaxial cable
Jacket:	Low smoke zero halogen material, (FRNC-C, IEC 60332-3-24)
CPR Classification:	Dca, s2, a1, d1
Overall diameter:	4.6 ±0.3mm
Impedance:	75 ±1% ohms
Capacitance:	56pF/m nominal
Return loss:	26dB nom. 50-300 MHz 22dB nom. 300-3000 MHz 18dB nom. 3000-3500 MHz 15dB nom. 3500-5000 MHz
Attenuation:	MHz dB/100m 10 5.1 100 11.4 200 15.7 750 30.2 1500 42.4 3000 61.3 6000 89.4 9000 109.5 12000 126.4
Weight:	3.2kg/100m
Reel length:	1000m
Cut lengths:	Available in any multiple of 1 metre

Manufactured by Draka, part of the Prysmian group of companies.

'SDV' and 'LFH' are registered trademarks of Canford Audio PLC.